

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

1 Identification of the substance/mixture and of the company/undertaking · Product identifier • Trade name: NO NONSENSE ZINC GALVANISING SPRAY · Article number: CE021 · Relevant identified uses of the substance or mixture and uses advised against · Application of the substance / the preparation Paint • Details of the supplier of the safety data sheet · Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL-8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com • Further information obtainable from: QHSE Department • Emergency telephone number: Tel: +31 (0)561 694400 (08.00 / 17.00) 2 Hazards identification · Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Aerosol 1 H222 Extremely flammable aerosol. GHS09 environment Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. GHS07 Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xi; Irritant R36: Irritating to eyes. F+; Extremely flammable R12. Extremely flammable. N; Dangerous for the environment R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. *R66-67*: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. (Contd. on page 2) Page 2/11


Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

Trade name: NO NONSENSE ZINC GALVANISING SPRAY



Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

Trade name: NO NONSENSE ZINC GALVANISING SPRAY

		td. of pag
CAS: 115-10-6	dimethyl ether	25-50
EINECS: 204-065-8	\bullet F+R12	
	🛞 Flam. Gas 1, H220	
	Press. Gas, H280	
CAS: 67-64-1	acetone	20-25
Enters: 200 002 2	$\stackrel{\text{\tiny R}}{\bullet} F R I I$	
	R66-67	
		-
	 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 	
<u> </u>	V ·	5.10
CAS: 7440-66-6	zinc powder -zinc dust (stabilized)	5-10
EINECS: 231-175-3		-
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	5-10
EINECS: 265-199-0		
	🗙 Xi R37	
	N R51/53	
	R10-66-67	
	Carc. Cat. 2, Muta. Cat. 2	
	🚸 Flam. Liq. 3, H226	-
	Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	STOT SE 3, H335+H336	
CAS: 7429-90-5	aluminium powder (stabilized)	5-10
EINECS: 231-072-3		
	🚸 Flam. Sol. 1, H228	-
CAS: 1330-20-7	xylene	2.5-5
EINECS: 215-535-7		2.0 0
	Xi R38	
	R10	
	Flam. Liq. 3, H226	-
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 95-63-6	▼	1 2 5
	1,2,4-trimethylbenzene	1-2.5
EINECS: 202-436-9		
	Xi R36/37/38	
	N R51/53	
	R10	-
	Flam. Liq. 3, H226	
	Aquatic Chronic 2, H411 Acute Terry 4, H222, Shin hmit, 2, H215, Euro hmit, 2, H210, STOT SE	
	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE	
	3, H335	
CAS: 108-67-8	mesitylene	0.1-1
EINECS: 203-604-4	Xi R37	
	N R51/53	
	<u>R1</u> 0	
	🛞 Flam. Liq. 3, H226	1
	Aquatic Chronic 2, H411	
	5TOT SE 3, H335	1
	SICI SE 5, 11555	

Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

Trade name: NO NONSENSE ZINC GALVANISING SPRAY

	(Con	td. of page 3
CAS: 98-82-8	cumene	0.1-1%
EINECS: 202-704-5	Xn R65 Xi R37 N R51/53 R10	
	 Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335 	-
CAS: 103-65-1	propylbenzene	0.1-1%
EINECS: 203-132-9	Xn R65 Xi R37 N R51/53 R10	
	 Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335 	-

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
 Keep away from ignition sources.
 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.

(Contd. on page 5)

GB

Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

(Contd. of page 4)

Trade name: NO NONSENSE ZINC GALVANISING SPRAY

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** No special measures required. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric

lights. Do not pierce or burn, even after use.

· Conditions for safe storage, including any incompatibilities

- Storage:
- *Requirements to be met by storerooms and receptacles:* Store in a cool location. Observe official regulations on storing packagings with pressurized containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.

Protect from heat and direct sunlight.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

· Ingred	ients with limit values that require monitoring at the workplace:
115-10	-6 dimethyl ether
WEL ()	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm
67-64-1	l acetone
WEL ()	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm
1330-2	0-7 xylene
WEL ()	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
95-63-6	6 1,2,4-trimethylbenzene
WEL ()	Long-term value: 125 mg/m ³ , 25 ppm ILV
· Additio	nal information: The lists valid during the making were used as basis.
• Person • Genera Keep a Immedi Wash h	are controls al protective equipment: al protective and hygienic measures: way from foodstuffs, beverages and feed. iately remove all soiled and contaminated clothing bands before breaks and at the end of work. inhale gases / fumes / aerosols.

(Contd. on page 6)

⁻ GB

Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

Trade name: NO NONSENSE ZINC GALVANISING SPRAY

(Contd. of page 5)

Avoid contact with the eyes.

- Avoid contact with the eyes and skin.
- Respiratory protection: Not required.
- Protection of hands: Not required.
- Material of gloves Not required.
- Penetration time of glove material Not required.
- Eye protection:



Tightly sealed goggles

Information on basic physical and che	mical properties
General Information	
Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour: Odour threshold:	Characteristic Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	< 0°C (< 32 °F)
	Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	235°C (455 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
Explosion limits:	
Lower:	2.6 Vol %
Upper:	18.6 Vol %
Vapour pressure at 20°C (68 °F):	4000 hPa (3000 mm Hg)
Density at 20°C (68 °F):	0.865 g/cm ³ (7.218 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Segregation coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	75.2 %

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

Trade name: NO NONSENSE ZINC GALVANISING SPRAY

		(Contd. of page 6)
· EU-VOC: · EU-VOC in %:	677.9 g/l 78.36 %	
• Solids content: • Other information	24.8 % No further relevant information available.	

10 Stability and reactivity

· Reactivity

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• **Possibility of hazardous reactions** No dangerous reactions known.

• Conditions to avoid No further relevant information available.

• *Incompatible materials:* No further relevant information available.

• Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values relevant for classification:			
115-10-6 dimethyl ether			
	LC50 / 4 h	308 mg/m3 (rat)	
67-64-1	acetone		
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	20000 mg/kg (rabbit)	
	LC50 / 4 h	39 mg/m3 (rat)	
64742-9	5-6 Solvent	naphtha (petroleum), light arom.	
Oral	LD50	3592 mg/kg (rat) (OECD401)	
Dermal	LD50	>3160 mg/kg (rab) (OECD402)	
	LC50 / 4 h	>15 mg/m3 (rat)	
1330-20	-7 xylene		
Oral	LD50	4300 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
	LC50 / 4 h	22.1 mg/m3 (rat)	
95-63-6 1,2,4-trimethylbenzene			
Oral	LD50	5000 mg/kg (rat)	
on the st on the e Sensitize Addition The prod	tal toxicolo g duct shows t	tant effect.	

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

Trade name: NO NONSENSE ZINC GALVANISING SPRAY

(Contd. of page 7)

12 Ecological information

Acquatic toxicity	:
115-10-6 dimethy	el ether
EC50 / 48 h	>4000 mg/l (daphnia magna)
67-64-1 acetone	
EC50 / 48 h	39 mg/l (daphnia magna)
LC50 / 48 h	2262 mg/l (daphnia magna)
LC50 / 96 h (stati	ic) 5540 mg/l (fish)
7440-66-6 zinc p	owder -zinc dust (stabilized)
EC50 / 48 h	2.8 mg/l (daphnia magna)
LC50 / 96 h	0.57 mg/l (daphnia magna)
64742-95-6 Solve	ent naphtha (petroleum), light arom.
EC50 / 24 h	150 mg/l (daphnia magna)
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	3.77 mg/l (fish)
1330-20-7 xylene	2
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)
Ecotoxical effect Remark: Toxic for Additional ecolog General notes: Water hazard cla Do not allow prov Danger to drinkin Also poisonous for Toxic for aquatic Results of PBT a PBT: Not applicat	or fish gical information: ss 2 (German Regulation) (Self-assessment): hazardous for water duct to reach ground water, water course or sewage system. ng water if even small quantities leak into the ground. or fish and plankton in water bodies. organisms nd vPvB assessment able.
vPvB: Not applic Other adverse eff Disposal const Waste treatment	fects No further relevant information available. iderations

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

(Contd. on page 9)

GB

Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

Trade name: NO NONSENSE ZINC GALVANISING SPRAY

(Contd. of page 8)

()	
ADR/RID class:	2 5F Gases.
Danger code (Kemler):	-
UN-Number:	1950
· Packaging group: · Hazard label	2.1
	e: 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· Limited quantities (LQ)	
Transport category	2
• Tunnel restriction code	D
· Maritime transport IMDC	<i>;</i> ;
· IMDG Class:	2.1
UN Number:	1950
Label Backaging group	2.1
Packaging group: EMS Number:	- F-D,S-U
Marine pollutant:	No
Proper shipping name:	AEROSOLS
· Air transport ICAO-TI an	nd IATA-DGR:
· ICAO/IATA Class:	2.1
· UN/ID Number:	1950
Label	2.1
· Packaging group: · Proper shipping name:	- AEROSOLS, flammable
	UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1
• Environmental hazards: Product contains environm	nentally hazardous substances: zinc powder -zinc dust (stabilized)
• Special precautions for us	
	ing to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 10) GB Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

Trade name: NO NONSENSE ZINC GALVANISING SPRAY

(Contd. of page 9)

· Code letter and hazard designation of product:



Xi Irritant F+ Extremely flammable

N Dangerous for the environment

· Risk phrases:

- 12 Extremely flammable.
- 36 Irritating to eyes.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 2 Keep out of the reach of children.
- *Keep away from sources of ignition No smoking.*
- 23 Do not breathe aerosol.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.
- · Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- Classification in accordance with Directive 75/324/EEC: Extremely flammable
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

Mere vant p	//// 45C5
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
	(Contd. on page 11)

Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2011

Version number 48

Revision: 01.06.2011

Trade name: NO NONSENSE ZINC GALVANISING SPRAY

R38	(Contd. of page 10)
	Irritating to skin.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
· Departm	ent issuing MSDS: QHSE Department
· Contact:	
Mrs. D. I	Kleistra
Mrs. A. v	an der Veen
· Abbrevia	tions and acronyms:
	rd européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International f Dangerous Goods by Road)
	ment international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the al Transport of Dangerous Goods by Rail)
	ernational Maritime Code for Dangerous Goods
	national Air Transport Association
	: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
	rnational Civil Aviation Organization Fechnical Instructions by the "International Civil Aviation Organization" (ICAO)
	ally Harmonized System of Classification and Labelling of Chemicals
	al concentration, 50 percent
	al dose, 50 percent
	ompared to the previous version altered.