## ATOM

### **EXTREMELY COMPACT AND COMFORTABLE**

Compact, lightweight and extremely comfortable thanks to its modular TPR frame, the ATOM offers enhanced protection. Use: safety goggles or face shield.



71 g



- + THERMO PLASTIC RUBBER (TPR)
- **+** OVERFLOW CHUTE FOR LIQUIDS
- **+** BALL-PIVOT
- **+** ADJUSTABLE STRAP
- + FITS OVER PRESCRIPTION GLASSES



# ATOM

### **EXTREMELY COMPACT AND COMFORTABLE**

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
АТОМ	Ventilated	ATOAPSI	2C-1,2 😭 1 BT KN C€	<b>≅</b> EN166 3 BT <b>C€</b>	Anti-scratch/Anti-fog(⁺ <b>;</b> )
	Visor for ATOM	ATOV	-	<b>≅</b> EN166 3 BT <b>C€</b>	-

#### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

- **B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

- K. Resistance to surface damage by fine particles (optional)
- N. Resistance to fogging (optional)

#### TECHNOLOGY

#### **∠**EQUALIZER

Equalizer is the high performance goggle system for protecting against fog. thanks to its double lens and regulation patch, the equalizer filters and regulates moisture levels in the goggles.

#### **♦**PL\TINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes.

In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

#### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- 3. Liquid droplets or splashes.
- **4.** Large dust particles > 5 microns.
- **5.** Gas and fine dust particles < 5 microns.
- B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

#### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.











Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél - 20 44 (2)202 204 4702

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk



# ATOM

### **EXTREMELY COMPACT AND COMFORTABLE**

CHARACTERISTICS					
LENSES	PC - 2,2 mm - Curve 5,5				
FRAME	TPR				
TEMPLES	Non applicable				
STRAP	Nylon				
FOAM	SBR				
SPARE LENSES	Non applicable				
TEAR OFF	Ref. TOATOM - Set de 5				

PACKAGING AND EAN13 CODE					
	ATOAPSI	ATOV			
Individual plastic bag	3660740006259	3660740006280			











01/10/2013

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

