541 HPPE Palm Plus





RECOMMENDED FOR THESE RISKS: Cold Cuts Abrasion Tears **RECOMMENDED FOR THESE LINES OF** WORK: Mechanical industry **Construction / Roofing** Metallurgical industry

Polyethylene knit Polyurethane coating

DESCRIPTION

- · Coated palm
- · Elasticated cuff
- · Standard finish
- · Without special treatment
- High performance polyethylene (HPPE)
- Anatomical shape
- · Seamless knit

BENEFITS

- · A flexible, light glove providing effective protection against cuts and very resistant to abrasion
- · Protects the hand from oils and abrasion while remaining elastic and breathable
- · Breathable back of hand to reduce perspiration
- Minimal allergy risks
- · Designed for easy movement and continuous wear
- · No irritation by seams in contact with the skin
- · Low-soil colour

AVAILABLE SIZES	6/S • 7/M • 8/L • 9/XL • 10/XXL
LENGTH Dependent on size, in mm (flat)	215-265
COLOUR OF SUPPORT/COATING	Black/black

RECOMMENDATIONS FOR USE

- · Do not use in cases of chemical, electrical or thermal risk
- · Highly traction resistant gloves, do not use if there is risk of being caught up in moving machines
- · Store away from light and humidity
- Wash at 40°C max, using a neutral detergent
- · Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions.

0 1 <u>2</u> 3 4



Globus Building 38 Wheel Forge Way Trafford Park, Manchester M17 1EH Tel: 0161 877 4747 Fax: 0161 877 4746 www.globus.co.uk

EC compliance certificate delivered by the notified body 0072 IFTH - Institut Français du Textile et de l'Habillement Avenue Guy de Collongue - 69134 Ecully Cedex - France

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

ABRASION CUTTING 0 1 2 3 4 0 1 2 3 4 5 TEARING PUNCTURE 123<u>4</u>

EN388 - 2003

Cat. II

[Updated 01/02/2010]

