317 Hi-Viz





RECOMMENDED FOR THESE RISKS: Cold Tears Micro-cuts

RECOMMENDED FOR THESE LINES OF WORK: Construction / Masonry, fabric

Construction / Public works

Construction / Exterior work

Globus

Globus Building 38 Wheel Forge Way Trafford Park, Manchester M17 1EH **Tel:** 0161 877 4747 **Fax:** 0161 877 4746 www.globus.co.uk

EC compliance certificate delivered by the notified body 0072 IFTH - Institut Français du Textile et de l'Habillement Avenue Guy de Collongue - 69134 Ecully Cedex - France

SHOWA BEST GLOVE

Tour Franklin, La Défense 8 - 92042 Paris La Défense - France Tel. +33 (0)1 55 62 14 20 - Fax +33 (0)1 55 62 14 29 info@showabestglove.eu · www.showabestglove.com

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Polyester knit Natural latex coating

DESCRIPTION

- Coated palm
- Elasticated cuff
- Rough finish over entire surface
- · Antibacterial and anti-odour treatment
- Anatomical shape
- Seamless knit
- · Phosphorescent marking after light-storage

BENEFITS

- A flexible, robust glove offering great dexterity and with good resistance to tearing
- Protects the hand in damp environments or against aggressive detergents or alcohols
- Breathable back of hand to reduce perspiration
- Surface provides tactile feel and better grip
- Greater hygiene
- · Designed for easy movement and continuous wear
- No irritation by seams in contact with the skin
- · Increased safety in poor lighting conditions

AVAILABLE SIZES	7/S • 8/M • 9/L • 10/XL
LENGTH Dependent on size, in mm (flat)	220-260
COLOUR OF SUPPORT/COATING	Fluorescent yellow/orange

RECOMMENDATIONS FOR USE

- · May cause latex allergies
- Do not use in cases of chemical, electrical or thermal risk
- Highly traction resistant gloves, do not use if there is risk of being caught up in moving machines
- Store away from light and humidity
- Wash at 40°C max, using a neutral detergent
- Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions.



ABRASION CUTTING 01234 012345



[Updated 01/02/2010]

