332 FOLDFLAT DUST MASKTM HORIZONTAL - FFP3 - VALVED

FOLDFLAT DISPOSABLE DUST MASK COMPLETE WITH AN FFP3 VALVE

RESPIRATORY PROTECTION

SPECIFICATION

TECHNICAL

MAN MADE FIBRES:

The mask has an ergonomic 3D design to fit most face shapes

INSTRUCTIONS FOR USE

Mask must be fitted in accordance with the instructions supplied Care must be taken to ensure that the correct mask type is selected for the work to be carried out

If in doubt as to the type of mask required seek professional guidance

PERFORMANCE

Offers an assigned protection factor (APF) of 20 x Workplace Exposure Limit (WEL) for fine non-toxic dusts, fibres, fumes and mists



DIMENSIONS OF MASK

Height: 135mm	
Width: 90mm	
Length: 175mm	
Weight: 33g (Approx)	

CLEANING & MAINTENANCE

Not Applicable - Disposable Product

Store the masks out of sunlight away from chemicals in a dry atmosphere

WALVE: Polystyrene exhalation

valve with rubber diaphragm

LIMITATIONS OF USE

Protection will only be offered if the mask is fitted correctly

The mask, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove mask and seek medical advice

Do not use where exposure to chemical gases may be experienced

Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres

Ensure good seal around the face is created before entering the hazard area

This mask is not designed to be worn by people with facial hair

The working life of the mask is nominally one day (this is based on an working day shift of 8 hours), however it may be affected by many factors, including work rate, airflow and concentration of any contaminant in the atmosphere. The mask should be changed immediately if, a.) Breathing difficulties due to clogging are experienced,

b.) Breakthrough of a contaminant is detected by smell, taste or any other means

c.) The mask becomes damaged

CONFORMITY & MARKINGS

Meets the FFP3 requirements of EN149

EC Certificate Number 560229, issued by BSi Product Certification

Markings: EN149:2001+A1:2009, 332 FFP3



MANUFACTURING FOR SAFETY
<u>www.jsp.co.uk</u>

UKSALES@JSP.CO.UK TEL: +44 (<u>0)1993 826050</u>

