

FEATURES

- Durable glove that remains flexible to temperatures as low as -50°C
- Encapsulated air molecules provide an inherent cushioning effect
- Secure grip in wet and dry environments
- Excellent dexterity, flexibility and durability
- Silicone free

DESCRIPTION

- Double insulated nylon liner with a HPT foam ¾ coating
- Additional foam coating across the palm, knuckles and fingers provides greater protection even in wet environments
- Warm and soft lining, anatomically designed for comfort and fit
- Treated with Actifresh to kill bacteria and promote freshness
- Black colouring to hide soiling



TECHNICAL DATA

AVAILABLE SIZES 8/M • 9/L • 10/XL

COLOUR OF LINER/COATING Black/Black



TYPICAL APPLICATIONS

- Offshore applications
- Oil & Gas cold storage
- Maintenance
- Utilities
- Packaging



Cat
CE II



EN 388 standard

Abrasion	3	EN388: 2003
Cut	2	
Tear	3	
Puncture	2	

EN 511 standard

A	0	EN511: 2006
B	2	
C	0	

Recommendations For Use

- Not recommended for use with liquid chemicals. Do not use near moving machines if there is a risk of entanglement. The glove may lose its insulative properties when becomes wet.
- Gloves should ideally be stored in cool, dry conditions in original packaging and away from direct sunlight.
- Both new and used gloves should be thoroughly inspected, especially after cleaning treatment, before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if re-use is intended in which case gloves should be cleaned as far as possible, provided no serious hazard exists, before removal from hand. Excess contamination should first be removed and the gloves may be decontaminated with mild detergent solution then rinsed with clean water and dried ideally with some air movement.