

# TRACKER

## HIGH PROTECTION

Ultra-comfortable and technical TRACKER provides protection from all mechanical risks and also chemical risks making it unique in the safety glasses range.

 PLATINUM



TRACPSF



Removable foam



52 g

### SUPPLIED WITH

Microfibre pouch  
ETUIFS

























- + UPPER PROTECTION**
- + SIDE VENTILATION**
- + REMOVABLE FOAM REINFORCEMENT WITH INDIRECT VENTILATION**
- + LOWER PROTECTION**
- + REMOVABLE ADJUSTABLE STRAP**

**bolle**  
SAFETY

# TRACKER

## HIGH PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>TRACKER</b> Temple version	 Clear	TRACPSI	2C-1,2  1 BT KN CE	 EN166 FT CE	Anti-scratch /Anti-fog (  )
	 Smoke	TRACPSF	5-2,5  1 BT KN CE	 EN166 FT CE	Anti-scratch /Anti-fog (  )
	 Yellow	TRACPSJ	5-1,4  1 BT KN CE	 EN166 FT CE	Anti-scratch /Anti-fog (  )
	 Welding shade 1,7	TRACWPCC2	1,7  1 FT CE	 EN166 FT CE	Anti-scratch
	 Welding shade 3	TRACWPCC3	3  1 FT CE	 EN166 FT CE	Anti-scratch
	 Welding shade 5	TRACWPCC5	5  1 FT CE	 EN166 FT CE	Anti-scratch
<b>TRACKER</b> Strap version	With strap	-	-	 EN166 3 4 BT CE	-
	Kit Foam and strap	TRACKITFS	-	-	-

### LENS MARKING


#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- B.** Impact à moyenne énergie, résiste à une bille de 6 mm et de 0,86 g à 120 m/s.

#### Others symbols:

- K.** Resistance to surface damage by fine particles (optional)
- N.** Resistance to fogging (optional)
- CE European standard  Manufacturer name


### TECHNOLOGY

#### PLATINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m<sup>2</sup>), to the most aggressive chemicals and delays the onset of fogging for 2 minutes.  
In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes.
4. Large dust particles > 5 microns.
- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
- CE European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.



Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

[bolle-safety.com](http://bolle-safety.com)

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY

# TRACKER

## HIGH PROTECTION

### CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC
STRAP	Nylon
FOAM	EVA

### PACKAGING AND EAN13 CODE

	TRACPSF
Individual plastic bag	3660740004835



01/10/2013

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

[bolle-safety.com](http://bolle-safety.com)

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY