



# Cut to Length Shower Curtain Rod

## This rod contains



1x 200cm Steel Rod



2x Wall Brackets



2x Wall Bracket Covers



2x 8 mm Screws



6x 25 mm Screws



6x 6.5 mm  
Plastic Wall Plugs


## Tool Required

- Small hacksaw
- Medium crosshead screwdriver
- Drill
- 6.5 mm drill bit suitable for wall type

## BEFORE YOU START


The screws and wall plugs supplied are only suitable for use in solid walls. If fitting to other types of wall ensure suitable fittings are used. Ensure there are no hidden service pipes and cables where you intended to drill. If drilling into ceramic tiles, use a special bit for ceramic tiles. Where possible, drill your holes between ceramic tiles in the grout.

## INSTALLATION





### Cutting to size

Measure the distance between the two walls and cut the rod to the overall length required, less 15mm.



### Wall Fixing

1. Measure drop of shower curtain to determine position of wall brackets (remember to allow for curtain hooks and enough overlap for bath or tray). Ensure there are no hidden pipes or cables in the wall where the brackets are to be positioned.
2. Place the first wall bracket in position and use as a template to mark screw holes. Drill holes using a 6.5mm drill bit and insert wall plugs. Fix wall bracket with screws provided.
3. Slide one of the wall bracket covers onto the rod, and insert the rod into this bracket. Note that the rod end must be pushed fully onto the wall bracket and locate firmly inside the outer ring.
4. Slide the second wall bracket cover onto the rod, and insert the rod into the second bracket. Position the second bracket. Repeating the above 2 steps to attach the second bracket to the wall.
5. Using provided screws 8mm to attach rod and brackets.
6. Push both wall bracket covers firmly into place.



## AFTER CARE

If in doubt, seek professional advice.

Never tug, pull down, or exert undue force on the shower curtain as this may loosen or break the wall fixings.

## GUARANTEE STATEMENT

This Product is Guaranteed to be free from faults arising from Manufacturing defects for a period of 2 Years from the date of purchase.

Please retain these instructions and your proof of purchase for future reference.