



TRASH 3 C5

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

- KOHLER air-cooled industrial engine
- Resistant pump-barrel
- Automatic priming
- Easy acces to the turbine
- Offeres accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE SPECIALIST

High performance under extreme conditions.



TRASH 3 C5

WATER PUMP SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	Extremely heavily sedimented water pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	1083,33
Outflow maximum (m3/h)	65
Lifting height (m)	25
Suction height (m)	8
Granulometry (mm)	20
Automatic priming	Yes
Fuel	Diesel Fuel
Tank (L)	4,30
75% cons. (l/h) *	1,40
75% Autonomy (h) *	3,10
Sound power level guaranteed LwA dB(A)	110
Acoustic pressure level @1m in dB(A)	95
Acoustic pressure level @7m in dB(A)	81

ENGINE SPECIFICATIONS

Engine brand	KOHLER
Engine ref.	KD350_C5
Engine Type	Diesel O.H.V.
Start	Starter
Oil shutdown	Non
Displacement (cm3)	349
Oil system capacity including filters (l)	1,20

DIMENSIONS AND WEIGHT

Length (cm)	71,50
Width (cm)	57
Height (cm)	59
Dry Weight (kg)	67

PACKAGING

Packaging type	Box
Length (cm)	73
Width (cm)	58
Height (cm)	59,50
Weight (kg)	79
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	132
weight of the packaged Pallet (kg)	326

ACCESSORIES SUPPLIED



Inlet filter

Fast connections



Circlips

User and maintenance manual

OPTIONS



RKB2	Trolley kit for the generating sets superior to 6kW
RH1	Cover for SDMO 's generating sets, welding sets and water pumps
R12	Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.