



Main

| | |
|---------------------------|--|
| Commercial Status | Commercialised |
| Device application | Distribution |
| Range | Easy 9 |
| Product or component type | Miniature circuit-breaker |
| Device short name | Easy9 MCB |
| Poles | 1P |
| Number of protected poles | 1 |
| [In] rated current | 32 A |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| Curve code | B |
| Breaking capacity | 6000 A Icn conforming to BS EN 60898-1 - 400 V AC 50/60 Hz phase to phase 6000 A Icn conforming to BS EN 60898-1 - 230 V AC 50/60 Hz phase to neutral |
| Suitability for isolation | Yes conforming to BS EN 60898-1 |

Complementary

| | |
|--|---|
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 230 V AC 50/60 Hz |
| Magnetic tripping limit | 3...5 x In |
| [Ics] rated service breaking capacity | 6 kA 100 % x Icu conforming to BS EN 60898-1 - 230 V AC 50/60 Hz |
| Limitation class | 3 conforming to BS EN 60898-1 |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz conforming to BS EN 60898-1 |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to BS EN 60898-1 |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | Without |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 2 |
| Height | 82 mm |
| Width | 18 mm |
| Depth | 72 mm |
| Product weight | 100 g |
| Colour | Grey RAL 7035 |
| Mechanical durability | 10000 cycles |
| Electrical durability | 4000 cycles |
| Connections - terminals | Tunnel type terminal, top or bottom rigid wire(s) 1...35 mm ² max Tunnel type terminal, top or bottom flexible wire(s) 1...25 mm ² max |
| Tightening torque | 3.5 N.m top or bottom |
| Earth-leakage protection | Without |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|------------------------------|
| Standards | BS EN 60898-1 |
| Product certifications | CE |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Pollution degree | 2 |
| Tropicalisation | 2 |
| Relative humidity | 95 % (55 °C) |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|--------------------------|---------------------------|
| Sustainable offer status | Not Green Premium product |
|--------------------------|---------------------------|