

### High Flow 20 micron spun bonded 20" filter cartridge

20" sediment cartridge to fit high flow filter housing (HF97). Removes sediment particles from drinking water down to 20 micron. Sediment removed from the water will be held inside the cartridge and so replacement at regular intervals is recommended. When first installing the cartridge it is good practice to run the tap for several minutes to flush through the media and remove any fine particles etc. left over from the manufacturing process.

#### SPECIFICATIONS

Nominal flow:	40 L/min
Recommended change out differential pressure:	1 BAR
Max water temp:	60°C
Diameter:	115mm
Height:	508mm
Micron rating:	20 micron
Material:	Polypropylene
Colour:	White
Suitable Filter Housing:	HF97



The differential pressure will increase the longer the cartridge is in service. The rate of that increase will be dependant on the quality of the incoming water.

#### Changing the filter cartridge

It is recommend that cartridges be changed at least every 3 to 6 months, or sooner if the quality or flow of the water falls below a reasonable level for your intended use, or if the differential pressure across the cartridge reaches 1 bar.

**Important Note:** Water supplies should always be verified as safe to drink by competent and qualified person(s)

**BWT UK Limited**  
**BWT House, The Gateway Centre,**  
**Coronation Road, High Wycombe,**  
**Buckinghamshire. HP12 3SU**

Tel: 01494 838100  
 Fax: 01494 838137  
 Email: [enquiries@bwt-uk.co.uk](mailto:enquiries@bwt-uk.co.uk)

[www.bwt-uk.co.uk](http://www.bwt-uk.co.uk)

BWT endeavour to ensure that the information in this document is correct and fairly stated, but does not accept any liability for any error or omission. The development of BWT products is continuous and published information may be out of date. Please check with BWT UK for final specifications - Pictures and diagrams are provided for guidance only.