2273 Series PUSH WIRE® Connectors

Quick, simple & re-usable



The WAGO 2273 Series PUSH WIRE® connector allows fast wiring for solid conductors safely due to the spring clamp connection.

- PUSH WIRE[®] connection, Re-usable
- 0.5 2.5mm², 24A rating, 2, 3, 4, 5 & 8 conductor
- Individual clamps allow for the use of conductors between 0.5 - 2.5mm² within the same connector
- International approvals

Suitable applications:-

- Lighting
- Power
- HVAC

& many more

2273 Selection case:- Part No. 887-100



40 x 2273-202 50 x 2273-203 50 x 2273-204 40 x 2273-205 20 x 2273-208





2273 Series PUSH WIRE® Connectors

Technical Data

0.5 - 2.5mm² "s" 450V/4 kV/2 24A







2273-202 2-conductor 3-conductor



2273-203





Dimensions (mm)





2273-204 4-conductor

2273-205 5-conductor

2273-208 8-conductor

Operating



1. Strip the conductor 11mm.

Accessories



2. Insert the conductor fully into the housing to complete the connection.



3. To remove, simply twist and pull the connector and conductor at the same time.



Easy testing, test point on the back of the housing.

Enclosure / Mounting Carrier The 2273 Series connectors should be used within a suitable enclosure. For larger enclosures a mounting carrier can be used.

For single-row Part No. 2273-500





In the mounting carrier, connectors may be commoned in longitudinal direction using an 862-482 jumper. Please note jumpers can not be removed.



Visual Wiring Inspection The transparent housing shows that the conductor is fully inserted; within the coloured base, the clear port shows that the conductor's strip length is correct. Conductors are correctly stripped if the clear port shows no bare conductor on the unprinted connector side. Image above shows the centre conductor with an exceeded strip length.

For further information on the 2273 Series please contact us.



WAGO Limited, Triton Park, Swift Valley Industrial Estate, Rugby, Warwickshire, CV21 1SG Tel: 01788 568 008 - Fax: 01788 568 050 - info@wago.ltd.uk - www.wago.ltd.uk