

Nest Thermostat E tech specs

Dimensions

Screen

Connectivity

Languages

Wireless

Warranty

Control systems

Power consumption



Colour White

and other factors. Learn more at nest.com/eu/savings

³Voice commands require a compatible home assistant.

²Mobile notifications and remote control require working Internet and Wi-Fi.

320 x 320 resolution at 182 pixels per inch 4.5 cm diameter

24-bit colour LCD

Temperature Sensors

Heat Link E

Humidity Proximity/Occupancy Ambient light

Size and weight Display with stand Mass (with cable): 408 g Width: 8.16 cm Height: 9.44 cm

> Diameter: 11.7 cm Mass: 117 g (without batteries) Trim Plate Diameter: 11.4 cm Mass: 22.3 g

Wi-Fi Internet connection

requirements Phone or tablet running iOS or Android Nest app

Dutch

English (US, UK)

French (Canada, France) Italian Spanish (North America, Spain)

Wireless Interconnect: 802.15.4 @ 2.4 GHz, Bluetooth low energy

Working Wi-Fi connection: 802.11b/g/n 2.4 GHz, 802.11a/n 5 GHz

Built-in, rechargeable lithium-ion battery Battery

2-year limited warranty.

For help, please visit nest.com/support.

Less than 1 kWh/month

In the box

Nest Thermostat E Terminal blocks Quick start guide Heat Link E Welcome Guide

Power adapter Trim plate Warranty Screws

Compatibility The Nest Thermostat E is compatible with

On/Off

OpenTherm

almost all central heating systems, including: Combi boilers Heat-only boilers

Heat pumps (heating only) Zoned systems District heating with electrical control valves

Certifications UL 60730-1, Standard for Safety Automatic Controls

UL 60730-2-9, Particular Requirements for Temperature-Sensing Controls