



### Main

Circuit breaker application	Distribution
Range	Acti 9
Product name	Acti 9 iC60 RCBO
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Device short name	IC60N RCBO
Poles description	1P + N
[In] rated current	45 A at 30 °C
Curve code	C
Earth-leakage sensitivity	30 mA
Breaking capacity	10000 A Icn at 150...230 V AC 50 Hz

### Complementary

Neutral position	Left
Number of protected poles	1
Network type	AC
Network frequency	50 Hz
[Ue] rated operational voltage	150...230 V AC 50 Hz
Trip unit technology	Thermal-magnetic
Residual current tripping technology	Voltage dependent
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A
[Icw] rated short-time withstand current	Icw: 250 A during 8/20 µs impulse withstand
Electrical insulation class	Class III
Limitation class	3
[Ui] rated insulation voltage	AC 50 Hz
[Uimp] rated impulse withstand voltage	4 kV
Suitability for isolation	Yes
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting support	DIN rail
Comb busbar and distribution block compatibility	YES
9 mm pitches	2
Height	93 mm
Width	18 mm
Depth	70 mm
Product weight	136 g
Colour	White
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Provision for padlocking	Padlockable
Locking options description	By padlocks
Connections - terminals	Screw clamp terminal (upstream) 1...16 mm <sup>2</sup> rigid Screw clamp terminal (upstream) 1...16 mm <sup>2</sup> flexible Screw clamp terminal (downstream) 1...10 mm <sup>2</sup> rigid Screw clamp terminal (downstream) 1...10 mm <sup>2</sup> flexible
Wire stripping length	14 mm for upstream connection 11 mm for downstream connection
Tightening torque	2 N.m upstream 2 N.m downstream
Earth-leakage protection	Integrated
Targeted country	UK

## Environment

Standards	IEC 61009-1 IEC 61009-2-2
Product certifications	SNI
IP degree of protection	IP20
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-30...70 °C

## Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------