Technical: wiring accessories

Lisse Screwless Deco

20AX DP switches

GGBL2011BSS

GGBL2010BSSS

GGBL2014WHBSS

Description

A high quality range of Lisse Screwless Deco accessories designed for both residential and commercial installations. This family of products benefits from all of the time and space saving solutions design features of the Lisse Screwless Deco range.

Fully manufactured in accordance with latest British & International Standards and third party certified.

Features & benefits

- Large plate footprint provides extra strength and reduces the need for additional decorating.
- 7mm raised edge offers easy installation for new buildings and retrofits.
- LED indicator.
- Minimum back projection frees up space in the back box for cabling.
- Backed out and captive screw terminals to allow for positive drive and speed of installation.
- Cable markings on all products with a moulded template to check the stripped wire length.
- Light grey back moulding colour for easier terminal identification.
- Square caged terminals with generous cable capacity.

Technical specifications	
	20AX DP switches
Voltage rating:	240V
Current rating:	20AX DP
Terminal capacity: (no. of cores to each terminal hole)	1.5mm² 5 2.5mm² 3 4.0mm² 2 6.0mm² 1
Dimensions:	87 x 87mm
Operating temperature:	Ambient temperatures not normally exceeding 25°C but occasionally reaching 35°C
Mounting box depth:	25mm
Fixing screws:	M3.5 x 25mm
Standard of compliance:	BS 60669-1

Technical: wiring accessories

Lisse Screwless Deco

20AX DP switches

Part code structure

Family
- **10** Plate switches
- **20** 20AX switches & flex outlets
- **30** Sockets
- **40** 50A switches & 45A control units
- **50** Fused connection units
- **60** Dimmers
- **70** Shaver sockets & data communication
- **80** Blank plates

Interior
- **B** Black
- **W** White

Finish
- **SS** Stainless Steel
- **PC** Polished Chrome
- **MB** Mocha Bronze
- **SB** Satin Brass
- **PB** Polished Brass
- **PW** Painted White
- **LC** Light Copper

GGBL**XX** **XX** **A** **YY** **S**

- GGBL: Lisse range
- XX XX: switched unswitched number of gangs number of ways
- A: Interior
- YY: Finish
- S: Packaging. Addition of **S** for point-of-sale/ display packaging

Dimensions

1 gang



Range

20AX & 32A switches	
GGBL2010AYYS	Control switch - 1 gang - 20AX DP
GGBL2011AYY(S)	Control switch - 1 gang LED indicator - 20AX DP
GGBL2014WHAYY	Control switch - 'Water Heater' - 1 gang flext outlet & LED indicator - 20AX DP

Steel mounting boxes	
SB251	1 gang 25mm deep

Configuration, packaging type and stock availability

Finishes	Inserts	Packaging option	Stock availability
Stainless Steel (SS)	White	Standard box	MTS
		Shelf ready box & display packaged	MTS
	Black	Standard box	MTS
		Shelf ready box & display packaged	MTS
Polished Chrome (PC)	White	Standard box	MTS
		Shelf ready box & display packaged	MTS
	Black	Standard box	MTS
		–	–
Satin Brass (SB)	White	Standard box	MTO
		–	–
	Black	Standard box	MTS
		Shelf ready box & display packaged	MTS
Mocha Bronze (MB)	White	–	–
		–	–
	Black	Standard box	MTS
		Shelf ready box & display packaged	MTS
Painted White (PW)	White	Standard box	MTO
		–	–
	Black	–	–
		–	–
Polished Brass (PB)	White	Standard box	MTO
		–	–
	Black	Standard box	MTO
		–	–
Light Copper (LC)	White	Standard box	MTO
		–	–
	Black	–	–
		–	–

MTO = made to order
MTS = made to stock