
Product data sheet Characteristics

NSYTBS19128

ABS box IP66 IK07 RAL7035 Int.H175W105D80 Ext.H192W121D87 Opaque cover H20





Main

| Range | Thalassa | |
|---------------------|--|---------------|
| Product name | Thalassa TBS | |
| Device application | Multi-purpose | |
| Category | Industrial box | |
| Height | 192 mm | (} !! |
| Width | 121 mm | |
| Depth | 87 mm | <u> </u> |
| Internal height | 175 mm | |
| Internal width | 105 mm | |
| Internal depth | 80 mm | |
| Enclosure mounting | Wall mounted | |
| Device composition | 1 x body | |
| | 1 x cover | |
| | 4 x cover screw | <u>.</u> 9 |
| Quantity per set | Set of 2 | |
| Body type | One piece moulded | |
| Type of front cover | Low plain cover | |
| Cover fixing | Plastic screws Outside sealed area : flat screwdriver captive screw | |
| Lock type | Outside sealed area : flat screwdriver captive screw | |
| Removable parts | Cover, by captive screws | |

Complementary

| Material | ABS (acrylonitrile butadiene-styrene) | |
|------------------------|---------------------------------------|---|
| Colour | Grey (RAL 7035) | |
| Standards | IEC 62208 | |
| Product certifications | DEMKO TÜV SEMKO | i |

| Electrical insulation class | Class II | |
|-------------------------------------|-------------------------------------|--|
| IP degree of protection | IP66 conforming to NEMA 4.4X | |
| IK degree of protection | IK07 conforming to IEC 62262 | |
| Fire resistance | 650 °C conforming to IEC 60695-2-11 | |
| Ambient air temperature for storage | -1540 °C | |
| Operating temperature | -2560 °C | |
| Product weight | 0.335 kg | |

Offer Sustainability

| Green Premium product | |
|--|--|
| Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity | |
| Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details | |
| Available | |
| Need no specific recycling operations | |
| | Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details Available |

Contractual warranty

| Warranty period | 18 months | |
|-----------------|-----------|--|
| | | |