



Aspirante

electric shower



Black Gloss

Dimensions given are approximate



Operating Features

- Swiv-let™ – 180° reversible water inlet providing Triton Swivel-fit™ flexibility for new or replacement installations
- Soft press illuminated power buttons
- Push button Start/Stop
- Power on indicator
- Low pressure indicator
- Rub clean showerhead – 5 spray pattern

Finish	Power	Code
Riviera Sand	8.5 kW	ASP08TLRSD
Riviera Sand	9.5 kW	ASP09TLRSD
Black Pearl	8.5 kW	ASP08TLPLBLK
Black Pearl	9.5 kW	ASP09TLPLBLK
White Gloss	8.5 kW	ASP08GSWHT
White Gloss	9.5 kW	ASP09GSWHT
Black Gloss	8.5 kW	ASP08GSBLK
Black Gloss	9.5 kW	ASP09GSBLK
Brushed Steel	8.5 kW	ASP08BRSTL
Brushed Steel	9.5 kW	ASP09BRSTL
Gun Metal	8.5 kW	ASP08GUNMTL
Gun Metal	9.5 kW	ASP09GUNMTL

Temperature Control	Stabilised
Power Ratings	8.5 kW, 9.5 kW
Inlet Connection	15mm compression
Water Entry Points	Top, bottom, side bottom, back (left hand side unit) Bottom, side bottom, back (right hand side unit)
Cable Entry Points	Top, bottom, side bottom, back (left hand side unit)
Outlet Connection	1/2" BSP
Plumbing System	Cold water only
Minimum Running Pressure/Flow	1 Bar @ 8 l/min
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI Kitemark
Guarantee	2 years