TECHNICALDATASHEET


ECHO ECHO SINK MIXER

ProductSpecification

Product Code:	EC SNK C
Finish:	Chrome
Product Type:	Contemporary
Construction:	Body is of brass construction
	and is designed to conform to BS EN 200
Valve Type:	$\frac{1}{2}$ turn $\frac{1}{2}$ " ceramic disc valves
Supply:	Suitable for all plumbing systems
Inlet Connections:	M12 x 15mm screw-in copper tail pipes
Water Pressure:	Min. 0.2 bar, Max. 8.0 bar







AdditionalInformation

- Dual flow.
- Supplied with metal levers & metal fixing nut.
- Chrome plated to BS EN 248.

Technical Advice:	For further information please call 0844 7016273 or email customercare@bristan.com.
Guarantee:	5 years covering manufacturing faults.

Compliance/Approvals

WRAS:

Certificate No. 0601116

FlowRates (litres per minute)

SystemPressure	0.2 bar	0.5 bar	1 bar	1.5 bar	2 bar
EC SNK C (mixed)	7.9	14.6	21.3	26.7	30.4

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG Telephone: 0844 701 6274 Facsimile: 0844 701 6275 Web Site: www.bristan.com Email: enquire@bristan.com



D3

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

AFTERCARE INSTRUCTIONS

Your fitting has a high quality finish and should be treated with care to preserve the visible surfaces.

All surface finishes will wear if not cleaned correctly, the only safe way to clean your mixer is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All bath cleaning powders and liquids will damage the surface of your fitting even the non scratch cleaners.

GUARANTEE

All products are manufactured to the highest standards and a 5 year guarantee covers any defect in manufacture.

NOTE: - the 5 year guarantee on the valve is invalidated if damaged by any waterborne debris.

PRODUCT CODE: EC SNK C

TELEPHONE HELP LINE: 0844 701 6273

Bristan Group Limited Birch Coppice Business Park Dordon Tamworth Staffordshire B78 1SG UK

Web Site: www.bristan.com Telephone: 0844 7016274 Facsimile: 0844 7016275 Email: enquire@bristan.com (FI EC SNK) (Rev. D2)

Fitting Instructions & Contents List

Please keep these instructions for future reference and for the ordering of spare parts.



Echo Sink Mixer


WATER PRESSURE


This mixer is suitable for use at a minimum supply pressure of 0.3 bar. However for optimum use both the hot and cold supplies should be reasonably balanced.

If the fitting is tank fed, then the minimum distance from the outlet of the nozzle to the underside of the cold tank should be approximately 3.0 metres to ensure adequate performance.

This mixer should be installed in compliance with Water Regulations. For further details contact your Local Water Authority.

CONTENTS





INSTALLATION

1. Identify all components and check for completeness, particularly before arranging fitting.

2. Fit the mixer body (1) to the sink using the 'C' plate fixing kit. The 'C' shaped rubber (4) and metal (5) washers go on the underside of the sink to be secured by the nut (3) and threaded rod (2).

3. Fit the tail pipes (6) to the fitting and connect the hot and cold supplies.

4. Fully open both valves (a) by turning handles (b), letting them run for a few minutes to check all joints and connections for leaks.

5. See over the page for aftercare instructions.

MAINTENANCE

If the fitting begins to drip:

1. Turn off the water supply.

2. Remove indices (d) and screw (c), then remove handle (b) by pulling from valve (a).

3. Using a suitable spanner, remove valve. Once removed, carefully clean seating, rubber washer and ceramic disc.

4. Replace all of the above then turn on the water supply.

5. If problem persists contact our helpline quoting the product code.

Please Note: -

In the unlikely event you find a part missing please contact our Customer Service Help line on 0844 7016273 or email enquire@bristan.com for immediate dispatch of part.