


12.14.

**303029 Glove Grey NBR Palm Coating on White Nylon Liner  
KeepSafe EN388 Cat 2**

**Users Guide: PPE Cat.2 Glove**

These products are classed as Personal Protective Equipment (PPE) by the European PPE Directive 89/686/EEC and have been shown to comply with this Directive through the Harmonised European Standard EN 388: 2003

The user must select the appropriate gloves for the task in hand.

Performance	303029
Mechanical Testing to EN388 	Glove Liner NBR Palm Coating on White Nylon Liner
Abrasion Resistance	4
Blade Cut Resistance	1
Tear Resistance	2
Puncture Resistance	1

Abrasion Resistance	Scale from 1 to 4
Blade Cut Resistance	Scale from 1 to 5
Tear Resistance	Scale from 1 to 4
Puncture Resistance	Scale from 1 to 4

They have been subject to a CE type examination performed by:  
Le CENTRE TECHNIQUE CUIR CHAUSSURE MAROQUINERIE - CTC  
4 Rue Hermann Frenkel -69367 LYON CEDEX 07  
Notified Body Number 0075

Glove Sizes (marked according to EN420): 8,9,10  
Not suitable for chemical applications

**Cleaning and Maintenance**

If required gloves can be cleaned with running water and allowed to drip dry.  
New and used gloves should be thoroughly inspected for damage before use.  
Information regarding protection refers to the working surface, ie the palm of the glove which has been submitted to testing.  
The protection levels indicated are only valid for new gloves.

The unstretched glove may not meet the minimum length requirements of EN420:2003 as they are designed to stretch to fit the hand



Registered Company No. 2902454  
TW7 4EX  
Supplier No. 301407

**WARNING**

These gloves have a high resistance to tearing and should **NOT** be used if likely to be caught in moving machinery  
EN420 Clause 7.3.7