## CONTOUR LIGHTWEIGHT AND EFFECTIVE

21 g of strength: sturdy, protective, stylish, comfortable and lightweight. CONTOUR is one of the top three best-selling models.

## 





SUPPLIED WITH Microfibre pouch

Microfibre pouch ETUIFS



+ NON-SLIP BRIDGE

**+** NON-SLIP TIPGRIP TEMPLES

+ ANTI-STATIC



# CONTOUR LIGHTWEIGHT AND EFFECTIVE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
CONTOUR	Clear	CONTPSI	2C-1,2 🗁 1 KN FT C €	🗁 EN166 FT <b>د є</b>	Anti-scratch/anti-fog(⁺ <b>₽</b> )
	Smoke	CONTPSF	5-2,5 🗁 1 KN FT C €	🗁 EN166 FT <b>( €</b>	Anti-scratch/anti-fog(+→)

### LENS MARKING

### **Optical class symbols:**

1. Continuous work

### Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

### Others symbols:

- K. Resistance to surface damage by fine particles (optional)
- N. Resistance to fogging (optional)
- C€ European standard ∑ Manufacturer name

### TECHNOLOGY

### 6 ESP

ESP, Extra Sensory Perception. An innovative coating to reduce dazzle and the harmful affects of blue light. B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

### 

This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd /  $m^2$ ), to the most aggressive chemicals and delays the onset of fogging for 2 minutes. In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

PACKAGING AND EAN13 CODE				
	CONTPSI	CONTPSF		
Individual plastic bag	3660740003241	3660740003258		

### 

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.

## FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for spectacles.
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- K. Resistance to surface damage by fine particles (optional)
- N. Resistance to fogging (optional)
- C€ European standard ☐ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 8			
FRAME	PC			
TEMPLES	Nylon + TPE			
STRAP	Non applicable			
FOAM	Non applicable			



Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél. : 00 33 (0) 4 78 85 23 64 Fax : 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY Tél. : 00 44 (0)208 391 4700 Fax : 00 44 (0)208 391 4733 e-mail : sales@bolle-safety.co.uk

bollé

03/12/2014

bolle-safety.com