350R Nitrile Grip





RECOMMENDED FOR THESE RISKS: Cold Tears Heavy perspiration **RECOMMENDED FOR THESE LINES OF** WORK: Mechanical industry Construction / Masonry, fabric Construction / Roofing Construction / Exterior work

Polyester/cotton knit Nitrile coating

DESCRIPTION

- · Coated palm
- · Elasticated cuff
- · Rough finish over entire surface
- · Antibacterial and anti-odour treatment
- · Anatomical shape
- · Seamless knit

BENEFITS

- · A flexible, robust glove offering great dexterity and with good resistance to tearing
- · Protects the hand from oils, hydrocarbons, grease and abrasion, with effective long lasting grip
- · Breathable back of hand to reduce perspiration
- · Surface provides tactile feel and better grip
- Greater hygiene
- · Designed for easy movement and continuous wear
- · No irritation by seams in contact with the skin

AVAILABLE SIZES	7/S • 8/M • 9/L • 10/XL
LENGTH Dependent on size, in mm (flat)	220-260
COLOUR OF SUPPORT/COATING	Grey/green

RECOMMENDATIONS FOR USE

- · Do not use in cases of chemical, electrical or thermal risk
- · Store away from light and humidity
- · Wash at 40°C max, using a neutral detergent
- Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions.

012345

0<u>1</u>234



Globus Building 38 Wheel Forge Way Trafford Park, Manchester M17 1EH Tel: 0161 877 4747 Fax: 0161 877 4746 www.globus.co.uk

EC compliance certificate delivered by the notified body 0072 IFTH - Institut Français du Textile et de l'Habillement Avenue Guy de Collongue - 69134 Ecully Cedex - France

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

ABRASION CUTTING 0 1 2 3 4 0 1 2 3 4 5 TEARING PUNCTURE 12<u>3</u>4

EN388 - 2003

Cat. II

[Updated 01/02/2010]



The Ultimate in Comfort and Dexterity