370 Black Assembly Grip





RECOMMENDED FOR THESE RISKS:

Cold

Abrasion

Oils

Heavy perspiration

RECOMMENDED FOR THESE LINES OF WORK:

Mechanical industry

Construction / Finishing work, tiling

Antiskid nylon knit Nitrile coating

DESCRIPTION

- · Coated palm
- · Elasticated cuff
- · Standard finish
- · Without special treatment
- · Anatomical shape
- · Seamless knit

BENEFITS

- A light, elastic low-lint glove, resistant to deformation and which keeps its shape longer
- · Protects the hand from oils, hydrocarbons, grease and abrasion, with effective long lasting grip
- · Breathable back of hand to reduce perspiration
- Minimal allergy risks
- · Designed for easy movement and continuous wear
- · No irritation by seams in contact with the skin
- · Low-soil colour

AVAILABLE SIZES	6/S • 7/M • 8/L • 9/XL • 10/XXL
LENGTH Dependent on size, in mm (flat)	200-260
COLOUR OF SUPPORT/COATING	Black/dark grey

RECOMMENDATIONS FOR USE

- · Do not use in cases of chemical, electrical or thermal risk
- Store away from light and humidity

EN388 - 2003

Cat. II

- · Wash at 40°C max, using a neutral detergent
- Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions.

ABRASION CUTTING 0 1 2 3 4 0 1 2 3 4 5

TEARING PUNCTURE 0<u>1</u>234

1234



Globus Building 38 Wheel Forge Way Trafford Park, Manchester M17 1EH Tel: 0161 877 4747 Fax: 0161 877 4746 www.globus.co.uk

EC compliance certificate delivered by the notified body 0072 IFTH - Institut Français du Textile et de l'Habillement Avenue Guy de Collongue - 69134 Ecully Cedex - France

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

[Updated 01/02/2010]

The Ultimate in Comfort and Dexterity