Zip InLine ES



Zip InLine ES4 under-sink electronic instantaneous water heater single outlet for hand washing. Compact design, featuring bare-wire for fast heat up, no standing heat losses. Easy to install and service.



| MODEL | ENERGY CLASS (H/C) | MIN/MAX FLOW RATE | NOMINAL POWER RATING KW | DIMENSIONS W X D X H |
|-------|--------------------|-------------------|----------------------------|-------------------------|
| ES4 | А | 1.5lpm / 2.5lpm | 4.4 kW @ 230V AC | 187mm x 80mm x 135mm |

Features and benefits

- Compact electronic instantaneous water heater with highly energy efficient bare wire system for economic water supply to a single outlet.
- The innovatively designed appliance heats the water automatically as it flows through, without wasting energy in standby operation.
- The heating power electronically compensates for variable inlet pressures and temperatures.
- Outlet temperature factory set to 38°C, but can be installer adjusted between 30°C to 43°C.
- Intended for use with taps having M22 /M24 nozzles.
- Easy to install and service.



Product detail

| Specification type | | |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Product code | ES4 | |
| Product name | InLine ES4 Instantaneous 4.4kW | |
| Energy efficiency class | А | |
| Element type | Bare Wire Heating System | |
| IP rating | 25 | |
| Capacity, weights & dimensions | | |
| Product weight | 1.3kg | |
| Filled Product Weight | 1.5kg | |
| Unit dimensions (W x D x H) mm | 187 x 80 x 135 | |
| Electrical | | |
| Nominal power rating | 4.4 kW @ 230V AC | |
| Nominal power supply | 230V | |
| Nominal rated current | 19 amps | |
| Plumbing | | |
| Wholesome water supply | Yes | |
| Water connection Size | 1/2"BSP | |
| Min water pressure | 0.45bar | |
| Max water pressure | 10bar | |
| Minimum flow rate I/pm | 1.5 | |
| Maximum flow rate I/pm | 2.5 | |
| Temperature increase at maximum flow rate | 26.2°C | |
| Minimum water resistance @ 150c | >800 | |
| Installation - Plumbing (H/C) | The appliance is intended for connection to the wholesome water supply. It should be installed by a suitably qualified person. The appliance may be used as an unvented installation (as shown in the diagram opposite) or as a vented installation. | |

The minimum water pressure will vary if a limescale filter is installed. Please contact us to discuss your requirements.



