
# Product data sheet Characteristics

# NSYTBS29248

# ABS box IP66 IK07 RAL7035 Int.H275W225D80 Ext.H291W241D88 Opaque cover H20





#### Main

Range	Thalassa	
Product name	Thalassa TBS	į į
Device application	Multi-purpose	
Category	Industrial box	, s
Height	291 mm	
Width	241 mm	ò
Depth	88 mm	
Internal height	275 mm	
Internal width	225 mm	0
Internal depth	80 mm	E
Enclosure mounting	Wall mounted	100
Device composition	1 x body 1 x cover	
	4 x cover screw	
Body type	One piece moulded	3
Type of front cover	Low plain cover	<u>.</u> T
Cover fixing	Plastic screws	
Lock type	Outside sealed area : flat screwdriver captive screw	1. 1. 2. 2.
Removable parts	Cover, by captive screws	- <u> </u>

### Complementary

Material	ABS (acrylonitrile butadiene-styrene)	
Colour	Grey ( RAL 7035 )	<u>.v</u>
Standards	IEC 62208	<u> </u>
Product certifications	DEMKO TÜV SEMKO	H. See Jacobs and See
Electrical insulation class	Class II	

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK07 conforming to IEC 62262
Fire resistance	650 °C conforming to IEC 60695-2-11
Ambient air temperature for storage	-1540 °C
Operating temperature	-2560 °C
Product weight	0.86 kg

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity	
REACh	Reference contains SVHC above the threshold - Go to CaP for more details  Go to CaP for more details	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

## Contractual warranty

	Warranty period	18 months
--	-----------------	-----------