


# GARAGE FLOOR TILE COMPANY

## GFTC Installation Guidelines

### TOOLS REQUIRED



Rubber Mallet



Chalk Line  
(optional)




Metal 1m Ruler


### CUTTING TOOLS (Choice)



Concave Blade  
(Utility Knife)



Jigsaw/Bandsaw  
Medium Blade



Guillotine

### TOOL TIPS

- + A Concave blade is curved, which makes cutting through tiles easier and safer. Avoid using a standard utility blade.
- + If using an electrical saw, use a rough/medium wood blade.
- + Always wear cutproof gloves.
- + When using a utility knife, score the cutting line several times and then bend/fold the tile back and forth until it breaks away.

### BEFORE YOU START

#### Heat Expansion

Tiles can expand and contract with changes in temperature. Areas of tile that are exposed to a heat source\* may expand causing tiles to lift. It is advisable to glue the tiles in these areas. We recommend using Uzin – MK 92 S, following the manufacturer's instructions.

#### \*Heat sources include but not limited to:

Direct sunlight (for example south facing shutters), ovens, furnaces, catalytic converters.

#### Outdoor Usage

The GFTC range is not suitable for outdoor use.

#### Heavy Trucks and/or Tight Turning Circles

Some vehicle designs present problems for the tiles e.g heavy trucks with small wheels or electric trucks with a battery located over the drive wheel. We strongly advise you to test the tiles with these types of vehicles before making a decision on which thickness to use. You should also consider using an adhesive.

#### Surface/Witness Marks

The method of manufacture may result in a witness mark\* being visible on the tile at the injection moulding point (centre) and around the edge of the tile. Please check the tiles before installation. If any markings are unacceptable, do not continue with installation as we will not accept responsibility for replacing or refunding the cost of any goods after 10m<sup>2</sup> or more have been installed.

\*A witness mark is an unavoidable alignment mark essential to the manufacturing process.

#### Staining From Rubber Tyres

It is possible for tyres and wheels to stain tiles. This is caused by a chemical reaction between the anti-oxidant used in some rubbers and the plasticizer used in vinyl. We strongly advise that you use darker tiles (black & graphite) to reduce the visibility of any stains. You should also consider the application of an approved sealer.


### PREPARATION

Allow tiles to acclimatise in the room for 24 hours. The minimum installation temperature is 15°C. If time is short, we recommend you split the tiles into smaller stacks (as seen in step 2) to speed up acclimatisation.


**Please Note:** We are unable to honour our warranty terms for installations that have taken place at temperatures below 15°C.

If installation **has** to take place at a temperature below 15°C, ensure the tiles acclimatise to the ambient temperature of the room before starting. Leave a larger expansion gap (than the recommended 5mm) between the tiles and any fixed point.


15 °C



**Step 1:** Sweep the floor to remove any loose impediments. Remove any high points in the floor and fill any holes with a suitable floor repair compound.



**Step 2:** Split the pallet into several stacks and place them around the area. They will acclimatise quicker, and will be easier to access during installation.



## STARTING OUT



**Step 1:** It's extremely important that tiles are kept square during installation. Every room has a different starting point. If you can, identify a straight wall or edge to work from. If you are using ramps, line them up first. Snap a **straight** chalk or laser line 1-1.5m away from the wall.

**Step 2:** Begin fitting the tiles together creating one row against the straight line. Adjust the position of the row carefully along the line considering the cuts to be made on either side.

**Step 3:** Add two more rows and shuffle the tiles ensuring they are as straight as possible and flush against the chalk/laser line.




**Step 4:** Continue to add tiles forming a pyramid (Refer to the numbering system below).



**Step 5:** Continue to build the staggered pyramid by adding one full size tile to both ends of every row.


When you can no longer lay any more full sized tiles, cut the remaining tiles to fit using the cutting instructions below.



**Step 6:** Clean the floor thoroughly after installation. We recommend you finish with caulk and/or skirting boards.


## CUTTING

**Step 1:** To make a cut, turn a tile over and place it on top of an installed tile. Push it against the wall or object as shown below.




**Step 4:** Join the two marks together with a metal ruler to create a cutting line.

**Step 2:** Every tile has small **bumps between** each joint. Slide the tile left or right until you see the first bump on the tile underneath.



**Step 5:** Cut the tile using your preferred method. When the tile is turned over it should fit leaving a 5mm gap between the edge of the tile and the wall.

**Step 3:** Mark the back of the tile where it lines up with the highest point of the bump. Do the same for the other side of the cut (it should already line up with a bump).



**Step 6:** Clean the floor thoroughly after installation.

## INDENTATIONS

Occasionally, you may notice indentations after applying a lot of weight to our floor tiles over a small area (e.g. motorcycle stands, machinery feet and vehicle jacks).

The tiles are designed to encourage movement when subject to heavy point loads. This is to prevent the tile from breaking or snapping under pressure.

The tiles will always return to their normal form once the weight has been removed, so this is nothing to be concerned about.

They may take longer to reform in colder weathers, however the process can be sped up by using a hot air gun or by placing a damp cloth over the tile and running an iron over the cloth (ensure the cloth stays damp).

## STAINS & SCRATCHES

All hard or resilient flooring will be prone to scratches and staining from rubber tyres.

To protect your floor we recommend using an approved sealer.

If you have any concerns about fitting your floor, you can contact us here:

**+44 (0)1582 310 705**  
**info@gftcompany.com**

## FOR THE PERFECT FINISH

- + Leave an expansion gap (min 5mm) between the tiles and any fixed point
- + Don't force tiles together - if they don't fit together easily, something is wrong
- + Undercut wooden doorjamb and slip the tiles underneath
- + Use ramps to create safe transitions into the room

**GARAGE FLOOR**  
**TILE COMPANY**