

LINING PAPER - 20m DOUBLE ROLL

Anaglypta®

Since 1887

2000 GRADE

Finest Quality & Performance Rolled Into One

*Better on
rough walls*

RETFORD WALLCOVERINGS LTD



5 060075 555459



Retford Wallcoverings Limited, Unit 28,
Corringham Road Industrial Estate,
Gainsborough, DN21 1QB
15

EN 15102 : 2007
Lining Paper

- COVERS IMPERFECTIONS
- ALLOWS WALLS TO BREATHE
- EASY TO APPLY
- EXCELLENT SURFACE FOR PAINT
- CONTAINS NO PVC
- PAPER FROM WELL MANAGED SOURCES
- FIRE RATED



free match



paste the paper



strippable

11.2m² 0.56 x 20m

Lining

Consumer Helpline +44 (0) 1427 616597 www.erfurtmav.com

Application Instructions for Anaglypta Label Lining Paper

- 1) Make sure application surfaces are sound, clean and dry. Absorbent surfaces (e.g. new plaster) should be sized. Painted surfaces should be lightly sanded.
- 2) Anaglypta Label Lining offers two surface finishes. The outer surface of the roll offers a finish that disguises brush and roller tracks whereas the inner surface is smoother.
Please ensure that all lengths are pasted on the same side.
- 3) Mark a straight line on the wall to position the first length, by using a plumb line (please note that the lining paper should ideally be applied at 90° to the final wallcovering if it is to be used as a base for decorative paper).
- 4) Measure and cut lengths allowing extra for trimming at either end.
- 5) Apply the ready mixed adhesive evenly ensuring the edges are covered.
- 6) Fold lengths but do not crease and leave each length to soak for the same period of time until pliable, we recommend 12-15 minutes.
- 7) Apply the first length to the guideline. Smooth down with brush and trim. Remove any adhesive from the face of the paper using a sponge and clean water.
- 8) Butt join subsequent lengths and avoid overlapping.
- 9) Allow to dry completely before applying final wallcovering or coating with emulsion, normally at least 24 hours.

Adhesive

We recommend using a good quality ready mixed adhesive to hang this product as they generally have a superior bond strength.

NB; If decorative wallpaper is to be applied over the lining paper it is advisable to use a paste that is also recommended for the decorative wallpaper.

Inspection of rolls

We make every effort to ensure our wallcoverings are perfect but variations sometimes occur. Before hanging check rolls are undamaged. Please retain all labels until decorating is complete, we will require them if you have a problem. We recommend after hanging 2 or 3 drops that you inspect the result before continuing. We cannot accept claims for consequential loss in respect of defects apparent prior to hanging or overhanging with decorative wallpaper. No claims in excess of one roll can be allowed for defects which are visible at the time of hanging. If a fault is found, please return any defect roll/s with label(s) to where it was purchased. This does not affect your statutory rights.

Warning

To minimise the hazard in the event of fire, do not apply wallcoverings over expanded polystyrene veneers and ensure the wallcoverings are always firmly stuck down as loose wallcoverings may contribute to the hazard. Surfaces painted prior to 1960 may contain lead pigments and special precautions should be taken when preparing these surfaces.



Tips to achieve a perfect finish with Anaglypta Lining

Preparing surfaces for decorating using Europe's most popular branded wallpaper. Easy to hang, allows wall to breathe.

RETFORD WALLCOVERINGS LTD

PROFESSIONAL QUALITY WALLCOVERINGS

Gainsborough, DN21 1QB, England