



Main

Range	Easy9
Device application	Distribution
Product or component type	Empty consumer unit
Enclosure type	Metal enclosure
Number of 18 mm modules per row	12
Provided equipment	Earth/Neutral terminal block Busbar neutral cable

Complementary

Enclosure mounting	Surface
Total number of 18 mm modules	24
Number of horizontal rows	2
Number of ways	22 ways (outgoer)
Enclosure material	Metal
Type of front cover	Plain
[In] rated current	100 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Type of rail	DIN
Cable entry	Knock-out
Cable cross section	1...25 Mm ² incoming
Comb busbar and distribution block compatibility	YES
Net weight	7.5 Kg
Height	312.4 Mm
Width	522.4 Mm
Depth	112 Mm
Colour	White (RAL 9003)

Environment

Standards	BS 7671 BS EN 61439-3
Product certifications	UKCA
IP degree of protection	IP3x (with closed door) IP2x (with open door)
IK degree of protection	IK05
Overvoltage category	II

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7.9 Kg
Package 1 Height	11.2 Cm
Package 1 width	31.24 Cm
Package 1 Length	52.24 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**