



## Main

Range	Easy9
Device application	Distribution
Product or component type	Empty consumer unit
Enclosure type	Metal enclosure
Number of 18 mm modules per row	12
Provided equipment	Earth/Neutral terminal block Busbar neutral cable

## Complementary

Enclosure mounting	Surface
Total number of 18 mm modules	36
Number of horizontal rows	3
Number of ways	34 ways (outgoer)
Enclosure material	Metal
Type of front cover	Plain
[In] rated current	100 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Type of rail	DIN
Cable entry	Knock-out
Cable cross section	1...25 Mm <sup>2</sup> incoming
Comb busbar and distribution block compatibility	YES
Net weight	10.5 Kg
Height	312.4 Mm
Width	780.4 Mm
Depth	112 Mm
Colour	White (RAL 9003)

## Environment

Standards	BS 7671 BS EN 61439-3
Product certifications	UKCA
IP degree of protection	IP3x (with closed door) IP2x (with open door)
IK degree of protection	IK05
Overvoltage category	II

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	10.9 Kg
Package 1 Height	11.2 Cm
Package 1 width	31.24 Cm
Package 1 Length	78.04 Cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**