



### Main

Range	Easy9
Product or component type	Comb busbar
Total number of 18 mm modules	12

### Complementary

Number of ways	Incomer: 2 ways N + L Outgoer: 10 ways N + L
Connection pitch	Outgoer: 9 mm Incomer: 18 mm
Connector type	Pin
Insulation	Insulated
Device presentation	Cuttable
Provided equipment	4 tooth covers 2 end-pieces
[Ie] rated operational current	100 A
[Ue] rated operational voltage	230 V AC
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 KV
Mounting mode	Horizontal
Mounting location	Top
Height	253 Mm
Width	39.4 Mm
Depth	44.2 Mm
Net weight	0.1 Kg
Colour	White (RAL 9003)

### Environment

Standards	IEC 61439-3
Product certifications	UKCA
Fire resistance	960 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	130.0 G
Package 1 Height	4.42 Cm
Package 1 width	3.94 Cm
Package 1 Length	25.3 Cm
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Weight	4.76 Kg
Package 2 Height	15 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**