


DESCRIPTION

16 different ways of use:




- 1 x 180° straightedge
- 1 x 90° angle
- 4 x 45° angle (16-10-8-5 mm)
- 3 x convex shapes (r = 18-5-3 mm)
- 7 x concave grooves (30-25-20-15-10-8-6 mm)
- Swallow-tail tool (tight corners, hard to reach areas)

WHAT'S NEW? The FUGI Kit helps to achieve clean profiles and makes a permanent seal. A releasing agent (soapy water) is not needed to apply the soft caulking mass (silicone). This process results in better adhesion and prevents mould from forming underneath. In the event that the profile application is not perfect, it is possible to remake isolated parts without having to remove the entire profile.

What kind of sealants? Silicone, acrylic, polyurethane... Actually all sealants can be applied: sealing and flexible grouts can be made with our FUGI.

What kind of surfaces? Can be used on all smooth, rough or uneven surfaces. Working on extreme rough surfaces will wear out your FUGI faster!

HOW TO USE: Choose the caulking line shape from 16 profile possibilities. Apply corresponding amount of caulking mass on a distance of 60-120 cm (it is easier to work step by step, by only applying for short distances). Make sure both FUGI edges touch both surfaces. Slightly press the FUGI and pull.



IMPORTANT:

**Always use the smooth FUGI edge for spreading!
Start again behind the point at which you stopped
with a new line section.**

Bridging across a vertical grout: If you hold the FUGI at a slight angle, you cross over the grout-line and doing so you will keep a uniform grout-pattern profile.

Corners: Start first with the vertical wall- grout lines and let them bond. After bonding, you work on the floor-grout starting out of the corners in both directions.

Intersection: Cover one grout with masking tape. This way, you can cross over the other one.

Cleaning of FUGI: Wipe the excess sealant off the FUGI with household paper towel. Should this be forgotten, simply rub the tool across a rubber-like surface.

Removal of old grouts: Remove old caulking carefully with a caulking removal knife with saw blade. What- ever is left on tiles or other smooth surfaces can be removed with a scraping blade. On soft surfaces a scraping blade could scratch, may be it's better to use here a chemical silicone remover.

IMPORTANT: When removing old mildew stained grouts or caulks, wear a protective mask (to avoid the danger of infection). Use an anti-mildew treatment on the affected area. Be sure the surface your work on is dry and free of oil or grease before restart caulking.



Made in Germany by

CRAMER GmbH · Salzstrasse 8 A · D 85622 Feldkirchen
phone: +49 (0)89 99909770 · fax +49 (0)89 99909777

U.K. Distributor:

Cramer U.K. Ltd. · Somerset BS28 4UY
fax: 01934-713377 · <http://www.diybathrepair.com>