Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	PHILIPS
--------------------------------	---------

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

_	•			
Tyna	Λt	light	source	٠.
IVDE	vı	HEILL	JUUILE	- •

LED	Non-directional or directional:	NDLS
B22		
MLS	Connected light source (CLS):	No
No	Envelope:	-
No		
No	Dimmable:	No
	B22 MLS No No	MLS Connected light source (CLS): No Envelope: No

Product parameters

Parameter		Value	Parameter	Value
		General product p	arameters:	
<u> </u>	mption in on- 100 h), rounded st integer	11	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	1 055 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pressed in W	oower (P _{on}),	11,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expres	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	110	Spectral power	See image
dimensions	Width	60	distribution in the	in last page
without	Depth	60		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	75
		Chromaticity coordinates (x and y)	0,458
Parameters for LED and OLED lig	ht sources:	,	
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,93		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

