



ITEM	DESCRIPTION	QTY
1	TAP BODY	1
2	INLEG ELBOW	2
3	FLANGE	2
4	WASHER (ANTI-ROTATIONAL)	2
5	WASHER	2
6	FIXING NUT	2

UNIVERSAL FITTING INSTRUCTIONS

Bridge Sink Mixer with Pillar Legs

BEFORE YOU START

This mixer is suitable for use at water supply pressures of 0.1 bar (min) to 7 bar (max).

If the tap is installed into a low pressure (tank fed) system, the minimum height from the outlet of the nozzle to the underside of the water tank should be at least 1.8 metres to ensure adequate performance.

This product must be connected to the water supply in accordance with the Water Supply (Water Fittings) Regulations 1999, and also to comply with UK Building Regulations. If you are in any doubt about these requirements, contact a qualified plumber, your local Water Company or the Water Regulations Advisory Service (WRAS).

- Identify all components and check pack contents.
- TURN OFF WATER MAINS SUPPLY.** The mains stopcock is usually situated where the supply enters the building.
- It is also recommended that the water heating arrangements are turned off.
- Drain the cold and hot water system. It is recommended to ensure complete drainage, that all taps are open. There is no need to drain the heating system.

INSTALLATION

- Fit Flanges (3) to Inlet Legs (2). Ensure both Flanges are fitted to the same position on the Inlet Legs.
- Fit Inlet Legs (2) to the Tap Body (1). Ensure that the Rubber Washer is fitted between the Inlet Leg (2) and the Tap Body (1). Tighten by hand.
- Fit Tap Body Assembly (1) onto Sink.
- Fit Anti-Rotational Washers (4) over Inlet Elbows (2). Then fit Washers (5) & Fixing Nuts (6) to Inlet Elbows and tighten. **DO NOT OVERTIGHTEN.**
- Connect to the water supply using suitable plumbing joints.
- Turn on the mains water supplies and re-fill the system. Check for leaks immediately. It is always advisable at this stage to flush out the system. To do this, open both valves fully and allow water to flow for approx. 1 minute. This will remove any foreign matter within the installation.
- Finally turn on all the water heating arrangements.

AFTER CARE

To maintain the appearance of this fitting, ensure it is cleaned only using a clean soft damp cloth. A solution of warm water and mild liquid detergent may be used where necessary and then rinsed thoroughly. Abrasive cleaners or acidic cleaners **MUST NOT BE USED** under any circumstances. Avoid contact with solvents.