



JAW DROPPER OPERATING GUIDELINES

PLEASE FOLLOW THESE OPERATING TIPS WHEN USING YOUR JAW DROPPER

1. Each Jaw Dropper set has a wrench for use on basin taps and another for use on bath taps.
2. Each Jaw Dropper wrench has a different diameter jaw gap size at each end of the wrench. This is to enable them to be used on the majority of nuts available on the market. It is up to the user to decide which end best suits their application.
3. To tighten or loosen pipe union nuts, the sliding jaw must be up against the fixed jaw and locked in position with the screw.
4. The sliding jaw acts as a 'stop' to easily locate Jaw Dropper onto the pipe union nut.
5. **It is advisable to isolate the water supply and drain the system** when carrying out any work on pipe union nuts.
6. To tighten or loosen tap back nuts, the sliding jaw must be moved away from the fixed jaw to allow Jaw Dropper to locate onto the tap back nut.
7. It is possible to get to the tap back nuts without removing the pipe union nut and pipe.
8. When tightening a tap back nut on a tap that has worked loose, it is not always necessary to isolate the water supply and drain the system. However, you may wish to do so for safety. see image No.5

Patent Pending
Registered Design No. 4000508



www.armeg.co.uk

ARMEG Limited, Callywhite Lane, Dronfield S18 2XJ, England
T: 01246 411031 F: 01246 411662 E: sales@armeg.co.uk



