

## TR 2.36 C5

PORTABLE POWER

WATERPUMP Range AQUALINE INTENS

#### **PRODUCT ADVANTAGES**

- HONDA Professional Engine
- Resistant pump-barrel
- Automatic priming
- Easy acces to the turbine
- Offeres accessories

The AQUALINETM INTENS TR 2.36 H and TR 3.60 H models have a very high quality pump body and are designed for treating dirty water intensively and reliably. The front cover can be removed for quick cleaning, which is a considerable help for professionals. STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing

compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

#### Range AQUALINE INTENS

Designed for water with low solid content.



# TR 2.36 C5

## WATER PUMP SPECIFICATIONS

Range	AQUALINE INTENS		
Type liquid	Heavily sedimented water pump		
Suction diameter [mm]	50		
Backflow diameter (mm)	50		
Outflow maximum (L/min)	600		
Outlflow maximum (m3/h)	36		
Lifting height (m)	29		
Suction height (m)	8		
Granulometry (mm)	8		
Automatic priming	Yes		
Fuel	Petrol		
Tank (L)	2		
75% cons. (l/h) *	1		
75% Autonomy (h) *	2		
Sound power level guaranteed LwA dB(A)	103		
Acoustic pressure level @1m in dB(A)	87		
Acoustic pressure level @7m in dB(A)	72		

### ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX120_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	118
Oil system capacity including filters (I)	0.60

### DIMENSIONS AND WEIGHT

Length (cm)	46.80	
Width (cm)	36.20	
Height (cm)	39.80	
Dry Weight (kg)	23	

### PACKAGING

Packaging type	Box	
Length (cm)	48	
Width (cm)	38	
Height (cm)	41.50	
Weight (kg)	26.50	
Pallet type	120/80	
Number of box by pallet	12	
Pallet height (cm)	138	
weight of the packaged Pallet (kg)	328	



TR 2.36 C5 - PORTABLE POWER - WATERPUMP AQUALINE INTENS

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com



# TR 2.36 C5

	Inlet filter		80	Circlips
<b>A</b>	Screw-on connect	ors		User and maintenance manual
OPTIONS				
Taning the second	RBH1	Box of 24 o.5L	cans of oil or 20 1 L cans of oi	I (SAE 15W40)
	RBH0-5	Box of 24 0.5L	cans of oil or 20 1 L cans of oi	I (SAE 15W40).
	RHO	Cover for SDM	1O 's generating sets, welding s	sets and water pumps
	R11	Piping kit for 2	water pumps made up of 5m s	uction + 25m lift.
RÓP	R13	Rapid connect	ions kit for 2 water pumps.	



TR 2.36 C5 - PORTABLE POWER - WATERPUMP AQUALINE INTENS This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528. SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com